

B01WSA0-DE/B0310SA0-DE

Surge Protections (Essential)

Best Surge Protection
Capability for Home Device
with Maximum Flexibility



B01WSA0-DE



B0310SA0-DE

*These models are also available with white color



Surge
Protection



EMI and RFI
Filtration



Overload
Protection




Computer-grade
Protection




Best-in-class
Dustproof Design

Ideal for home and office, the Essential Series safeguards connected equipment against surge and spike. The essential surge protectors include surge protected outlets for distributing power to multiple devices. The products are designed with Metal Oxide Varistor (MOV) technology to absorb surge which is caused by storms and lightning, therefore offering protection for equipment and devices. They also provide overload protection, noise filters and computer-grade protection to enhance safety for your devices.



B01WSA0-DE



B0310SA0-DE

APPLICATIONS

- Home
- SOHO Office
- Office
- POS Systems
- Home Theater Systems
- Multimedia Devices
- Home Appliances
- Computers

SERIES FEATURES

- Surge Protection
- EMI and RFI Filtration
- Computer-grade Protection
- Best-in-class Dustproof Design



TECHNICAL SPECIFICATIONS

Model Name	B01WSA0-DE-B	B01WSA0-DE-W	B0310SA0-DE-B	B0310SA0-DE-W
Input				
Input Voltage Range (Vac)	250			
Maximum Input Current (A)	16		10	
Input Connector Type	Schuko			
Plug Style	-		Right Angle	
Power Cord Length (m.)	-		1	
Power On/Off Switch	-		Yes	
Output				
Overload Protection	Circuit Breaker			
Over Current Protection (A)	16		10	
Outlet(s) - Total	1		3	
Outlet Type	Schuko x 1		Schuko x 3	
Surge Protection & Filtering				
Surge Suppression (Joules)	1050		350	
Maximum Surge Voltage (V)	6000			
Maximum Surge Current (A)	22500		7500	
Maximum Surge Current (L-N, L-G, N-G) (A)	Line to Neutral (L-N):7500, Line to Ground (L-G):7500, Neutral to Ground (N-G):7500		Line to Neutral (L-N):7500	
Clamping Voltage (L-N, L-G, N-G) (V)	Line to Neutral (L-N):1200, Line to Ground (L-G):1200, Neutral to Ground (N-G):1200		Line to Neutral (L-N):1200	
Response Time (ns)	< 1			
EMI/RFI Filtration (Hz)	100KHz ~ 100MHz			
LED Indicators	Surge Protected			
Physical				
Form Factor	Wall Tap		Strip	
Enclosure Fire-resistance	Yes			
Keyhole Mounting Slots	-		Yes	
Safety Shutter	Yes			
Physical Size				
Dimensions (WxHxD) (mm.)	102 x 70 x 80		215 x 54 x 40	
Environmental				
Operating Temperature (°C)	0 ~ 35			
Operating Relative Humidity (Non-condensing) (%)	0 ~ 95			
Certifications				
RoHS	Yes			
Product Warranty	2			
Power Control Guarantee				
Connected Equipment Guarantee	Limited Lifetime			
CEG Amount	€ 25,000			

#All specifications are subject to change without notice. © 2018 Cyber Power Systems, Inc. All Trademarks are the property of their owners.

